



BB-16M Battery-Powered Fan

INDUSTRY LEADING TECHNOLOGY AND DESIGN

Powered by: MILWAUKEE® M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Batteries



- ✓ **48-Minute Run Time** at full speed and constant CFM with 2 batteries.
- ✓ **Removable Batteries**
Powered by 1 and up to 2 removable Milwaukee® M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Batteries.
- ✓ **Adjustable tilt** from +70° to -90° with locking system (18 settings) allows flat positioning to cover a utility hole)
- ✓ **Shore Power Ready**
- ✓ **Lightweight** highly durable build makes it easy to carry and deploy on site using shoulder strap.
- ✓ **Battery Management System** insures maximum performance and safety.
- ✓ **Active LED Lighting** Powerful LED lights positioned low for visibility below the smoke.
- ✓ **Proprietary NEO Technology** creates an oval air pattern that maintains an effective door opening seal and provides maximum air flow into a structure.



Active LED Lighting



+70° at -90° Tilt Range



Available Options

910-1817	BB-16 MILWAUKEE - Base Model - No Battery/No Charger
585-071	MILWAUKEE M18 12 Ah Lithium Ion Battery
585-072	MILWAUKEE Single Battery Charger
585-073	MILWAUKEE Multi-battery Charger 6-Port

Specifications

Motor	0.37 HP / 280W Variable Speed Drive BLDC Totally Enclosed, Air over IP66
Battery	1 and up to 2 Removable Milwaukee® M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Batteries
Ingress Protection	IP66
Drop Test	Designed to resist a Drop Test of 1.5M / 5'
Noise Level	79dB at 3m / 10'
Air Volume	9,707 CFM / 16,502 m³h
Weight	With batteries 48 lbs. / Without batteries 42 lbs.
Dimensions (L x H x D)	22"L x 21"H x 11"D
Propeller Diameter	16"
Run Time	48 Minutes at Full Speed with both batteries
Operating Temperature	-4°F to +122°F
Tilt Range	+70° at -90°
Warranty	TEMPEST BB-16 Milwaukee - Electronics & Motor (3 Years)
Manufacturer Warranty	Milwaukee® M18™ REDLITHIUM™ HIGH OUTPUT™ HD12.0 Batteries (3 Years)