



## VS1.3D Battery-Powered Fan

### INDUSTRY LEADING TECHNOLOGY AND DESIGN

Powered by: DEWALT® FLEXVOLT® 20V/60V MAX\* Batteries



- ✓ **40-Minute Run Time** at full speed and constant CFM
  - ✓ **AMCA Certified @ 9,614CFM**
  - ✓ **Removable Batteries** Powered by 1 and up to 3 removable DEWALT® FLEXVOLT® 20V/60V MAX\* 12.0 Ah Batteries.
  - ✓ **Shore Power Ready**
  - ✓ **Lightweight** welded tubular aluminum frame design makes it easy to roll or lift.
- US Patents: US 12,146,615, 11,624,471, 11,333,291, 10,837,592, D829,879
- ✓ **Battery Management System** insures maximum performance and safety.
  - ✓ **Small Footprint** half the size of a gas fan
  - ✓ **Active LED Lighting** Powerful LED lights positioned low for visibility below the smoke.
  - ✓ **Thin-Vane™ Air Straightener** reduces wasted airflow.



Active LED Lighting



Precise, Locking Tilt-Angles



Immediately Shore Power Ready

Our battery-driven series delivers a level of utility and performance found with no other battery-driven fan. But when you want to connect to power, Shore Power is standard on every Tempest Battery-Powered Fan that we build.



### Available Options

910-2010	VS1.3D DEWALT® no battery, no charger
910-2010A	Kit includes - 3 x 12Ah DEWALT Batteries & 1 Single-Bay Charger
910-2010B	Kit includes - 3 x 12Ah DEWALT Batteries & 4-Bay Charger
585-071	12AH DEWALT® batteries
585-041	9AH DEWALT® batteries
585-072	DEWALT® Single Battery Charger
585-073	DEWALT® 4-Bay Charger

### Specifications

Motor	0.87 HP / 744W Variable Speed Drive BLDC Totally Enclosed, Air over IP65
Battery	Removable DEWALT® FLEXVOLT® 20V/60V MAX* 12.0 Ah or 9AH Li-Ion (1 and up to 3)
Charging Time	100% Charge in 2-hours with External Optional Charger
Ingress Protection	IP65 (excludes DEWALT® Batteries)
Drop Test	Designed to resist a Drop Test of 1.5M / 5'
Noise Level	83.7dB at 3m-10'
Air Volume	9,614CFM / 16,334 m <sup>3</sup> /h AMCA Certified
Weight	With batteries 51 lbs. / Without batteries 41 lbs.
Dimensions (L x H x D)	Handle Down 25.5"x 23.75"x 15.25" Handle Up +4.9"
Propeller Diameter	18"
Run Time	Average run time at full speed 40 minutes with 3 x 12AH batteries
Operating Temperature	-5°F to +113°F
Tilt Range	-12.5° to +25° with Precise Tilt Points
Warranty	TEMPEST VS1.x Fan (5 Years), Electronics & Motor (1 Year)
Manufacturer Warranty	DEWALT® FLEXVOLT® 20V/60V MAX* 12.0 Ah Batteries (3 Years)