



NEO
LEADER Fan
EASY POW'AIR
TECHNOLOGY

GASOLINE-DRIVEN FAN **MT215 L**

Compact and lightweight: 44.7 lbs!

A very **concentrated and ultra-powerful** jet of air due to an optimal combination of:

- ▶ A high-strength propeller matched to the power of the engine
- ▶ A red double-layer monobloc shroud made of reinforced high-density polyethylene
- ▶ A high-tech composite grille

Positioning from 3 ft to 20 ft in front of a door without loss of power for:

- ▶ more space to move about
- ▶ less noise inside the building

With folding pull/steer handle for easier set-up

Precise tilt adjustment

from -10° to +20° with indicator for optimization of direction of air stream up entrance steps or down into a semi-basement

Protective frame

with gray epoxy coating

Stable & easy to handle with large rear wheels

Compact for easy storage in vehicle trunks

Characteristics

Model	MT215 L NEO
Reference	160.10.062N
Open air flow	19,940 CFM
PPV air flow according to AMCA	13,690 CFM
Weight (dry)	44.7 lbs
Dimensions L x H x D	20.9 x 19.5 x 21.9 inch
Propeller diameter	16.5 inch
Run time at full speed	1h40
Engine	HONDA GXH50 engine (4-stroke) 56% less CO than a 5 HP engine Assembly inspected and approved by Honda Motor Co., Ltd
Engine power	2.1 HP according to standard SAE J1349 of 2007
Noise level	84,5 dB at 10 ft
Ventilation type	PPV blowing
Application	Single door, e.g. house, small apartment block

Optional accessories:

High expansion foam adapter without coupling delivered with 114.8 ft of polyane plastic film duct (products with coupling: see p. 52)	160.20.105
Hour meter	160.20.135
16.4 ft ventilation duct	160.20.152

i Ventilation tactics in the catalogue or at www.LeaderNorthAmerica.com
 Freely downloadable interactive ventilation courses at www.leaderexpert.com
 As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice