Fighting for performance

INDUSTRY LEADING TECHNOLOGY AND DESIGN POWERED BY:

DEWALT® FLEXVOLT® 20V/60V MAX\* 12.0 Ah Batteries

# VS-1.2D TEMPEST TECH SERIES BATTERY POWER BLOWERS



Powered by 1 and up to 3 DEWALT® FLEXVOLT® 20V/60V MAX\* 12.0 Ah or 9Ah Batteries







# 40-Minute Run Time

With all 3 DEWALT® FLEXVOLT® 20V/60V MAX\* 12.0 Ah Batteries, the blower will run for an average of 40 minutes or you can run off of just 1 or 2 batteries.



# **Small Footprint**

This Blower is half the size of a gas blower. VS-1.2D Dimensions: L x H x D 22.88" x 24.4" x 12.25"



# **Removable Battery**

1 and up to 3 Lithium Ion Batteries in succession with 2-hour quick charge.



### **LED Flow-Path Lighting**

Powerful LED lights positioned low for visibility below the smoke.




# Only 51 lbs. w/ 3 Batteries

Only 41 lbs. without batteries. Lightweight welded tubular aluminum frame design makes it easy to deploy on site. *US Patent #: US 11,333,291 B2* 



### Ultra-Light™ Air Straightener

"Ultra-Light™ Grill designed to reduce wasted airflow. Forces the air to flow straight out.



# **(§**)

### 10887 CFM tested to AMCA Standards

The VS-1.2 series produces the Highest Air Flow available in any battery blower.



# **WARRANTY**

Blower: 5 Year Limited Warranty Battery: Separate manufacturers' warranty



### **Battery Management System**

The dynamic BMS built into the battery insures maximum performance and safety.



# **Conversion Kits Available**

Have an older VS-1 or VS-1.2? We have kits that can convert both the original VS-1 or VS-1.2 into DEWALT®-Powered Blowers

# tempest.us.com

# **TEMPEST TECH SERIES/TEMPEST POWER BLOWERS**

(D) (in) (in)

POWERED BY: DEWALT® FLEXVOLT® 20V/60V MAX\* Batteries

SPECIFICATIONS							
Air Volume	10,887 CFM (18497 m³/h)	Motor	0.87 HP / 744W Variable Speed Drive BLDC Totally Enclosed, Air over IP65				
Weight	With batteries 51 lbs. / Without batteries 41 lbs.	Battery	Removable DEWALT® FLEXVOLT® 20V/60V MAX* 12.0 Ah or 9AH Li-lon (1 and up to 3)				
Dimensions (L x H x D)	Handle Down - 22.88″L x 24.4″H x 12.25″D Handle Up +4.9″	Charging Time	100% Charge in 2-hours with External Optional Charger				
Propeller Diameter	18"	Ingress Protection	IP65 (excludes DEWALT® Batteries)				
Run Time	Average run time at full speed 40 minutes with 3 x 12AH batteries	Drop Test	Designed to resist a Drop Test of 1.5M / 5'				
Operating Temperature	-5°F to +113°F	Noise Level	83.7dB at 3m-10'				

AVAILABLE OPTIONS						
PART NUMBER	PRODUCT	INCLUDES				
910-1860	VS-1.2D - without battery or charger	Electric PPV Blower, Variable Speed Drive, 18" Impeller Brushless DC Electric motor, 1 Shoulder Strap, No charger, No battery				
910-1861	VS-1.2D - with 3 - 12AH DEWALT® batteries and 1 single-bay charger	Electric PPV Blower, Variable Speed Drive, 18" Impeller Brushless DC Electric motor, with 3 - 12AH DEWALT® batteries, 1 Shoulder Strap, 1 single-bay charger				
910-1862	VS-1.2D - with 3 - 12AH DEWALT® batteries and 4-bay charger	Electric PPV Blower, Variable Speed Drive, 18" Impeller Brushless DC Electric Motor, with 3 - 12AH DEWALT® batteries, 1 Shoulder Strap, 4-bay charger				
910-1863	VS-1.2D - with 3 - 9AH DEWALT® batteries and 1 single-bay charger	Electric PPV Blower, Variable Speed Drive, 18" Impeller Brushless DC Electric Motor, with 3 - 9AH DEWALT® batteries, 1 Shoulder Strap, 1 single-bay charger				
910-1864	VS-1.2D - with 3 - 9AH DEWALT® batteries and 4-bay charger	Electric PPV Blower, Variable Speed Drive, 18" Impeller, Brushless DC Electric Motor, with 3 - 9AH DEWALT® batteries, 1 Shoulder Strap, 4-bay charger				
610-1840	VS1 DEWALT® Conversion Kit	Includes Battery Mounting System, No Batteries, No Charger				
610-1841	VS1 DEWALT® Conversion Kit	Includes Battery Mounting System, 3 x 12Ah DEWALT® Batteries, and 1 single-bay charger				
610-1842	VS1 DEWALT® Conversion Kit	Includes Battery Mounting System, 3 x 12Ah DEWALT® Batteries, and 4-bay charger				

AVAILABLE ACCESSORIES						
585-040		DEWALT® FLEXVOLT® Li-lon Battery 12AH / 240 WH Average run time at full speed 40 minutes with 3 batteries (Run-time depending on battery condition).	585-046		Single Bay DEWALT® FLEXVOLT® Quick Charger	
585-041	A PARTIES AND A	DEWALT® FLEXVOLT® Li-lon Battery 9AH / 180 WH Average run time at full speed 30 minutes with 3 batteries (Run-time depending on battery condition).	585-047		Four Bay DEWALT® FLEXVOLT® Quick Charger	
725-070		Flex Tube Ducting	610-1801		Shoulder Carry Strap (1 is included with every VS1.2D)	
725-200		Rehab Misting Ring	300-141 / 300-142	K	Door Bar Holder and Bracket Set	
			300-187	MA	(2) Pack Glow Wedges	