



# LEADER SENTRY WIRELESS : STRUCTURE STABILITY MONITORING TELEMETER

## EARLY DETECTION AND ALERT OF MOVEMENT FROM THE STRUCTURE IT IS POINTED TO

LEADER SENTRY is a safety monitoring device which is portable and autonomous. It continuously detects slight movements at distance of any unstable structure or object. The structure is targeted by a harmless laser. In case of movement, The LEADER SENTRY immediately triggers a powerful siren for alerting the team working around about dangerous moves or imminent collapse.

It creates safe zones and secured working conditions for responders engaged on the rescue scene.

LEADER SENTRY can be positioned up to 50m distance from unstable structures. It will trigger a 105dB alarm in case of weak movement detected (from 2 to 100mm). It provides a 6h running time using dry cell batteries. Compact and lightweight: 3.8kg (laser + tripod). IP55 Ingress Protection will keep it reliable in any weather condition. Mainly used for outdoor large areas LEADER SENTRY can connect 2

wireless lasers together up to a 100m distance.

They can be supplied with an optional wireless remote control box with integrated siren. The siren can also be voluntarily activated to ask for evacuation. Being held by a supervisor it allows better management of the LEADER SENTRY lasers at distance.

Applications:

- Structural fires
- Road traffic collisions
- Collapsed structures
- Trench rescues
- Shoring systems movement
- Fragile structures during or after fire / flood incidents



# FEATURES AND BENEFITS



## Intuitive control board

Device offers 7 thresholds : 2, 5, 10, 20, 40, 70 and 100mm with 1mm accuracy. Information is displayed on an OLED screen with excellent clarity even in bright sunlight. Software is intuitive and buttons are easy to operate with gloves.



## 50m laser beam range

In addition to the 50m range, the harmless laser filters out any quick interruption of the laser beam by a bird or person passing through. This prevents from false alarms.



## Telescopic sight

Associated telescopic sight to pinpoint precisely target that needs monitoring. It is equipped with a 2.5x/10x focus and a Ø40mm objective lens.



## Audio and Visual alarms

In case the structure moves over the selected threshold, a 105dB audible alarm is triggered together with 3 powerful white flash blinking beacons to ensure working crew to hear and see the alert.



## Wireless connection


- 2 lasers can be wireless connected up to 100m from each other. This allows managing both lasers from one of them.
- An optional wireless remote control can be supplied to even better ease management at distance.



## Various power supplies

- 12 AAA alkaline supplied cell batteries provide 6h run time (9h with Lithium dry cells). Easy to find on the field and no transportation constraints compared to Lithium batteries.
- 110/240V 50/60Hz mains power supply that can also be plugged to 12/24V cigar lighter plug via an integrated adaptor.

# LEADER SENTRY FUNCTIONS



- 1 | OLED display
- 2 | Power On-Off
- 3 | Measurement units: mm or inches
- 4 | Display of the main parameters of both lasers beams at the same time. Also allows to deactivate the audible alarm for silent operations (the flashes remain active).
- 5 | Allows switching from one laser to another and thus making the settings on the manipulated laser or the remote one.
- 6 | Name of the laser being configured.

- 8 | Movable cursor representing the movement of the target.
- 9 | Laser quality measure permanently displayed
- 10 | Wireless connection quality level between lasers
- 11 | Reminder of the name of the laser physically handled. (LA1 or LA2)
- 12 | Battery level
- 13 | Bell indicating that monitoring is activated and that the alarm is ready to alert if the selected threshold is exceeded.

**Note:** An optional wireless remote control (RC) can be connected for better management.

- 7 | Distance between the laser and target (m or ft).

## CHARACTERISTICS

<b>Fire and Rescue applications</b>	■ Designed for use in large indoor and outdoor areas	<b>Monitoring technology</b>	■ Telemeter laser beam
<b>Design concept</b>	■ Laser head on tripod + warning alarm	<b>Accurate</b>	■ Accuracy: +/-1mm
<b>Monitoring method</b>	■ Detects distance difference	<b>Lightweight</b>	■ Laser: 2kg and Tripod: 1.8kg
<b>Positioning</b>	■ Placed at distance up to 50m from structure	● Remote control : 550g	● External rechargeable battery : 640g
<b>Safe zone to create</b>	■ Safe and easy implementation at distance from the dangerous structure	● Suction pad : 300g	■ Laser: H182 x D165 x W241 mm Tripod: H1785 mm unfolded / H190 mm folded
<b>7 thresholds</b>	■ 2, 5, 10, 20, 40, 70, 100 mm (or inches)	<b>Compact</b>	● Remote control : H33 x D128 x L192 mm
<b>See live monitoring</b>	■ Distance displayed at all time	● External rechargeable battery : H70 x D95 x L175 mm	● Suction pad : H120 x Ø98 mm
<b>Visual alarm</b>	■ 3x 100 Lumens white flash lights for 360° visibility	<b>Strong material</b>	■ High impact resistant thermoplastic elastomer
<b>Audible alarm</b>	■ 105dB alarm or Mute	<b>Run time with dry cell batteries</b>	■ Alkaline (supplied): >6h ■ Lithium (not supplied): >9h ■ Rechargeable NiMH (not supplied): >7h
<b>Wireless connection</b>	■ 2.4GHz Zigbee technology / 100m range / 2 lasers + 1 optional remote control	<b>Remote control run time</b>	● 55h
<b>Alarm relay</b>	■ Optional remote control integrating 80dB alarm. Output connection for more powerful remote loud speaker (not supplied).	<b>External battery run time</b>	● 45h (charging time 5.5h)
<b>Robust</b>	■ 2m drop test onto concrete	<b>Wide operating t°C range</b>	■ Laser: -10°C to +50°C. Remote control: -20°C to +50°C
<b>Water resistant</b>	■ IP 55	<b>Wide storage t°C range</b>	■ Laser and Remote control: -20°C to +50°C
<b>Dry battery cells power supply</b>	■ 12x 1.5V AAA type cells	<b>Protection for carriage</b>	■ <b>Single:</b> Padded bag / H170 x D200 x L360 mm Empty: 1.3kg / Full: 6kg. No hard case. <b>Double:</b> Back pack / H225 x D440 x L575 mm Empty: 3.2kg / Full: 12.4kg Optional IP67 hard case: Empty: 7.3kg / Full: 19.7kg <b>Single Full:</b> Padded bag / H170 x D200 x L360 mm Empty: 1.3kg / Full: 8kg. No hard case. <b>Double Full:</b> IP67 hard case / H245 x D525 x L655 mm Empty: 7.3kg / Full: 22.5kg
<b>Main power supply</b>	■ 110/240V transformer for use with mains plug, combined with 12-24V cable for use in cigar light plug (as standard).	<b>Warranty</b>	■ 24 months
<b>Battery power supply</b>	● External NiMH rechargeable battery (up to 45h run time)	<b>Made in France</b>	■ Designed and manufactured in France
<b>Sentry single</b>	■ 1 SENTRY in transport bag with standard accessories		
<b>Sentry double</b>	■ 2 SENTRY in back pack with standard accessories		
<b>Safety dual pack</b>	■ 1 WASP + 1 SENTRY in back pack with standard accessories		

### LEGEND

- As standard
- Option adaptable afterward

## AVAILABLE MODELS

<b>LEADER SENTRY SINGLE</b>	D11.06.020	1 telemeter with telescope, tripod, ball-joint mount, 4 battery packs to receive 12 AAA supplied alkaline batt., 110/220V mains power supply with international adaptors, 12/24V cable cigar lighter adaptor, straps with hooks, padded transport bag, user manual, quick start guide
<b>LEADER SENTRY SINGLE FULL KIT</b>	D11.06.020F	1 telemeter with telescope, tripod, ball-joint mount, 4 battery packs to receive 12 AAA supplied alkaline batt., 110/220V mains power supply with international adaptors, 12/24V cable cigar lighter adaptor, straps with hooks, padded transport bag, user manual, quick start guide, 1 remote control, 1 external rechargeable battery and charger
<b>LEADER SENTRY DOUBLE</b>	D11.06.022	2 telemeters with telescope, tripod, ball-joint mount, 8 battery packs to receive 24 AAA supplied alkaline batt., 2x 110/220V mains power supply with international adaptors, 2x 12/24V cable cigar lighter adaptor, 2 straps with hooks, 1 back pack, user manual, quick start guide
<b>LEADER SENTRY DOUBLE FULL KIT</b>	D11.06.022F	2 telemeters with telescope, tripod, ball-joint mount, 8 battery packs to receive 24 AAA supplied alkaline batt., 2x 110/220V mains power supply with international adaptors, 2x 12/24V cable cigar lighter adaptor, 2x straps with hooks, 1 back pack stowed into IP67 hard case, user manual, 1 quick start guide, 1 remote control, 2 external rechargeable batteries and 2 chargers
<b>SAFETY DUAL KIT WASP + SENTRY</b>	D11.06.032	1 WASP unit, 4x C supplied alkaline batteries, Attachment accessories (1 Clamp, 1 Sucking pad, 1 Strut bracket, 1 Multi-purpose plate, 1 String with carabiners), user manual. + 1 SENTRY telemeter with telescope, tripod, ball-joint mount, 4 battery packs to receive 12 AAA supplied alkaline batt., 110/220V mains power supply with international adaptors, 12/24V cable cigar lighter adaptor, straps with hooks, user manual. ALL stowed into a back pack (hard case in option).
<b>Option</b>	D11.06.023	External rechargeable NiMH battery (1 per laser). IP67. Comes with its cable
<b>Option</b>	D11.06.025	Charger for external rechargeable NiMH battery
<b>Option</b>	D11.06.021	Wireless remote control with integrated audio alarm (6AA alkaline cell batteries supplied)
<b>Option</b>	D11.06.026	Clutch bag for wireless remote control
<b>Option</b>	D11.06.024	Hard case. IP67. Sized for SENTRY Wireless DOUBLE models and Safety Dual Pack

## ACCESSORIES



**Telescopic tripod** (comes as standard)  
Extended height up to 1.8m and comes with 3D attachment piece to orientate laser head in any direction. It integrates a hook underneath tripod top for hanging a ballast to ensure better stability.



**Adjustable strap** (comes as standard)  
Strap with hooks for attaching load or fixing the tripod to objects on ground to secure the stability.



**External rechargeable battery** (optional). This battery is NiMH type (no lithium, no transportation constraint!) and provides 45h run time. IP55. The 110/240V charger comes with international adaptors and must be ordered together with it.



**Remote control** (optional)  
Allows setting and stopping lasers at distance. Relays the audio triggered alarm of the lasers via the integrated speaker (80dB). Powered by 6 AA dry cell batteries providing 55h run time.



**Clutch bag** (optional)  
It allows to easily carry the remote control.



**Transport**  
1/ SENTRY SINGLE comes with a classic padded transportation bag.  
2/ SENTRY DOUBLE comes with a back pack to allow easy walking transportation on the field.  
3/ An optional hard case is available (shockproof, IP67) for SENTRY DOUBLE and SAFETY DUAL PACK.