

NEW & AVAILABLE! INDUSTRY LEADING TECHNOLOGY AND DESIGN POWERED BY: HURST[®] Jaws of Life[®] E3[™]/EWXT[™] Batteries

VS-1.3H **TEMPEST TECH SERIES BATTERY POWER BLOWERS**



Powered by 2 HURST® Jaws of Life® E3™/EWXT™ 9Ah or 5Ah Rescue Batteries.





35-Minute Run Time

With 2 removable HURST[®] Jaws of Life[®] E3[™]/EWXT[™] 9Ah or 5Ah Rescue Batteries, the blower will run for an average of 35 minutes.



Removable Battery Powered by 2 removable HURST[®] Jaws

of Life[®] E3[™]/EWXT[™] 9Ah or 5Ah Rescue Batteries.



Only 50 lbs. w/ 2 Batteries Only 45 lbs. without batteries. Lightweight welded tubular aluminum frame design makes it easy to deploy on site. US Patent #: US 11,333,291 B2



Battery Management System The dynamic BMS built into the battery insures maximum performance and safety.



10887 CFM tested to AMCA Standards The VS-1.3 series produces the Highest Air Flow available in any battery blower.



Increased depth for greater stability Large 6" wheels for ease of rolling over obstacles



LED Flow-Path Lighting Powerful LED lights positioned low for visibility below the smoke.



Ultra-Light™ Air Straightener Ultra-Light[™] Grill designed to reduce wasted airflow. Forces the air to flow straight out.



WARRANTY

Blower: 5 Year Limited Warranty Battery: Separate manufacturers' warranty

NOTE: Unit specification subject to change without notice.



SPECIFICATIONS

Airflow	10,887 CFM (18,497m ³ /h) (calculated according to AMCA 240)	Motor	0.8 HP / 600W Variable Speed Drive BLDC Totally Enclosed, Air over IP65
Weight	With batteries 50 lbs. / Without batteries 45 lbs.	Battery	Removable HURST® Jaws of Life® E3™/EWXT™ 9Ah or 5Ah Rescue Batteries.
Dimensions (L x H x D)	Handle Down - 23.75″L x 25″H x 15.25″D Handle Up +4.9″	Charging Time	100% Charge in 2-hours with External Optional Charger
Propeller Diameter	18″	Ingress Protection	IP65 (excludes HURST® Jaws of Life® E3™/EWXT™ 9Ah or 5Ah Rescue Batteries)
Run Time	Average run time at full speed 35 minutes with 2 x 9AH batteries	Drop Test	Designed to resist a Drop Test of 1.5M / 5'
Operating Temperature	-5°F to +113°F	Noise Level	83.7dB at 3m-10′

PRODUCT PART NUMBER					
PART NUMBER	PRODUCT	INCLUDES			
910-1880	VS-1.3H - without battery or charger	Electric Tall PPV Power Blower, Fold down Handle, Variable Speed Drive, 18" Impeller BLDC 0.8HP, 1 Shoulder Strap, No batteries, No Charger.			

AVAILABLE ACCESSORIES

725-070		Flex Tube Ducting	610-1801		Shoulder Carry Strap (1 is included with every VS1.3H)
725-049L	(THE COM	Rehab Misting Ring	300-141 / 300-142	A Company of the second	Door Bar Holder and Bracket Set
			300-187		(2) Pack Glow Wedges