



VENTMASTER® 572HD

GAS-POWERED FIRE RESCUE CHAINSAW
FROM TEMPEST TECHNOLOGY



Steel Deflector Plate



Tool-Less "KIS-40"
Aluminum Depth Gauge



Raptor Carbide Chain

Tested in the world's most rugged environments, the 572HD® is ready for demanding work by Fire Fighters. At just 14.5lbs, the 572HD® has a better power-to-weight ratio and 12% higher culling capacity. Excellent cooling and heavy-duty filtration maximize reliability, while a smart design accommodates longer guide bars.

- ☑ **Tool-Less "KIS-40" Depth Gauge** accurately controls cutting depth, protects operator and safely speed cut and eliminates the need to "roll the rafters."
- ☑ **Ventmaster® COBALT Guide Bar** Extremely hard COBALT alloy at the wear points provide excellent wear galling and impact resistance very high operating temperatures.
- ☑ **Raptor Carbide Chain** Engineered withstand the rigors of fire and rescue operations. Features an "open dual raker" to protect the carbide cutters and control the depth of cut through anything.
- ☑ **Centrifugal Force Air Cleaning System** Clean intake air means longer intervals between cleanings, longer runs at full power, less chain damage, smooth operation and reduced engine wear



Available Options

TV400-084	572HD-16.404 - Ventmaster 572HD, 16" with Chain, No Depth Gauge
TV400-087	572HD-20.404 - Ventmaster 572HD, 20" No Chain, No Depth Gauge
TV400-083	572HD-20.404 - Ventmaster 572HD, 20" with Chain, No Depth Gauge
TV400-081	572HD-16-DG.404 - Ventmaster 572HD, 16" with Chain, Depth Gauge
TV400-080	572HD-20-DG.404 - Ventmaster 572HD, 20" with Chain, Depth Gauge
TV400-086	572HD-16-DG.404 - Ventmaster 572HD, 16" No Chain, Depth Gauge
TV400-088	572HD-16.404 - Ventmaster 572HD, 16" No Chain, No Depth Gauge
TV400-085	572HD-20-DG.404 - Ventmaster 572HD, 20" No Chain, Depth Gauge
TV415-001	16" Loop for Ventmaster Saws
TV415-002	20" Loop for Ventmaster Saws
TV425-040	16" Cobalt Guide Bar for Ventmaster
TV425-042	20" Cobalt Guide Bar for Ventmaster
TV410-003	KIS-40 Complete Chainsaw Depth Gauge

Specifications

Powerhead Model	HUSQVARNA® 572 XP® (X-TORQ®) with Autotune™ Carburetor
Power Output	5.8 HP / 74.3 kW
Displacement	4.3 ci / 70.6 cc
16" Guide Bar - Product Weight	Dry - 23 lbs. / 10.5 kg / Wet - 25.7 lbs. / 11.2 kg
20" Guide Bar - Product Weight	Dry - 24 lbs. / 11 kg / Wet - 26 lbs. / 11.5 kg
16" Guide Bar Product Height / Width / Depth	12.5 in / 37 in / 12.5 in. / 318mm / 838 mm / 318mm
20" Guide Bar Product Height / Width / Depth	12.5 in / 37 in / 12.5 in. / 318mm / 940 mm / 318mm
Chain Speed	70.2 feet/second / 21.4 meters/second
Chain Speed @ 133%	93.5 feet/second / 28.5 meters/second
Fuel Capacity	0.185 gallons / 0.70 liters
Recommended Fuel	(R+M)/2 - 87 Octane Gasoline or Better, 2 Stroke Oil Mixed 50:1
Chain Type	Raptor Carbide Chain 0.404 pitch / 0.063 gauge
Cutter Type	Carbide Chisel Type - Open Dual Raker
Guide Bar Wear Protection	Flame Hardened with Cobalt Alloy Nose Inserts
Noise Level at Operator	105 db