



BB16 Battery-Powered Fan

INDUSTRY LEADING TECHNOLOGY AND DESIGN


Powered by: Tempest's proprietary Lithium-Ion 12.5Ah Battery



- ☑ **30-Minute Run Time** at full speed and constant CFM
- ☑ **Removable Batteries**
Removable Lithium-Ion with 3 hour quick charge.
- ☑ **Shore Power Ready**
- ☑ **Lightweight** highly durable build makes it easy to carry and deploy on site using shoulder strap.
- ☑ **Battery Management System**
insures maximum performance and safety.
- ☑ **Built-In Charger** - Battery charges while in use.
- ☑ **Active LED Lighting** Powerful LED lights positioned low for visibility below the smoke.
- ☑ **Proprietary NEO Technology**
creates an oval air pattern that maintains an effective door opening seal and provides maximum air flow into a structure.



Active LED Lighting



Built-In Charger



+65° at -90° Tilt Range



Available Options

910-1815A	BB-16 STANDARD - 1 Battery/Internal Charger Only
910-1815B	BB-16 STANDARD PLUS - 1 Battery/ External Quick Charger
910-1815C	BB-16 DELUXE - 2 Batteries/ Quick Charger
585-007	Li-Ion GEN2 Battery 12.5 AH IP65-Rated
585-037	External Quick Charger GEN 2 for BB-16 Battery

Specifications

Motor	1.34 HP / 1000W Variable Speed Drive BLDC Totally Enclosed, Air over IP66
Battery	Removable GEN 2 12.5AH / 585WH Li-Ion
Charging Time	100% Charge in 3-hours with External Optional Charger
Ingress Protection	IP66
Drop Test	Designed to resist a Drop Test of 1.5M / 5'
Noise Level	76.3dB at 3m / 10'
Air Volume	10,940 CFM
Weight	With battery 51 lbs. / Without battery 41 lbs.
Dimensions (L x H x D)	22"L x 21"H x 11"D
Propeller Diameter	16"
Run Time	30 Minutes at Full Speed
Operating Temperature	-4°F to +130°F
Tilt Range	+65° at -90°