




VS1.2D Battery-Powered Fan

INDUSTRY LEADING TECHNOLOGY AND DESIGN

Powered by: DEWALT® FLEXVOLT® 20V/60V MAX* Batteries



- ✓ **40-Minute Run Time** at full speed and constant CFM
- ✓ **Removable Batteries** Powered by 1 and up to 3 removable DEWALT® FLEXVOLT® 20V/60V MAX* 12.0 Ah Batteries.
- ✓ **AMCA Certified @ 9,614CFM**
- ✓ **Shore Power Ready**
- ✓ **Lightweight** welded tubular aluminum frame design makes it easy to roll or lift. US Patent #: US 11,333,291 B2
- ✓ **Battery Management System** insures maximum performance and safety.
- ✓ **Small Footprint** half the size of a gas fan
- ✓ **Active LED Lighting** Powerful LED lights positioned low for visibility below the smoke.
- ✓ **Thin-Vane™ Air Straightener** reduces wasted airflow.



Active LED Lighting



Precise, Locking Tilt-Angles



Immediately Shore Power Ready

Our battery-driven series delivers a level of utility and performance found with no other battery-driven fan. But when you want to connect to power, Shore Power is standard on every Tempest Battery-Powered Fan that we build.



Available Options

910-1860	VS1.2D DEWALT® no battery, no charger
910-1860A	Kit includes - 3 x 12Ah DEWALT Batteries & 1 Single-Bay Charger
910-1860B	Kit includes - 3 x 12Ah DEWALT Batteries & 4-Bay Charger
910-1860C	Kit includes - 3 x 9Ah DEWALT Batteries & 1 Single-Bay Charger
910-1860D	Kit includes - 3 x 9Ah DEWALT Batteries & 4-Bay Charger
585-071	12AH DEWALT® batteries
585-041	9AH DEWALT® batteries
585-072	DEWALT® Single Battery Charger
585-073	DEWALT® 4-Bay Charger
610-1840	VS1 DEWALT® Conversion Kit (to convert VS1.2 STANDARD battery fan)

Specifications

Motor	0.87 HP / 744W Variable Speed Drive BLDC Totally Enclosed, Air over IP65
Battery	Removable DEWALT® FLEXVOLT® 20V/60V MAX* 12.0 Ah or 9AH Li-Ion (1 and up to 3)
Charging Time	100% Charge in 2-hours with External Optional Charger
Ingress Protection	IP65 (excludes DEWALT® Batteries)
Drop Test	Designed to resist a Drop Test of 1.5M / 5'
Noise Level	83.7dB at 3m-10'
Air Volume	9,614 CFM (16,334 m³/h)
Weight	With batteries 51 lbs. / Without batteries 41 lbs.
Dimensions (L x H x D)	Handle Down - 23"L x 24.5"H x 12.5"D Handle Up +4.9"
Propeller Diameter	18"
Run Time	Average run time at full speed 40 minutes with 3 x 12AH batteries
Operating Temperature	-5°F to +113°F
Tilt Range	-12.5° to +25° with Precise Tilt Points