




VS1.3H Battery-Powered Fan

INDUSTRY LEADING TECHNOLOGY AND DESIGN

Powered by: HURST® Jaws of Life® E3™/EWXT™ Batteries



- ✓ **35-Minute Run Time** at full speed and constant CFM
- ✓ **Removable Batteries** Powered by 2 removable removable HURST® Jaws of Life® E3™/EWXT™ 9Ah or 5Ah Rescue Batteries
- ✓ **Shore Power Ready**
- ✓ **Lightweight** welded tubular aluminum frame design makes it easy to roll or lift. US Patent #: US 11,333,291 B2
- ✓ **Battery Management System** insures maximum performance and safety.
- ✓ **Small Footprint** half the size of a gas fan
- ✓ **Active LED Lighting** Powerful LED lights positioned low for visibility below the smoke.
- ✓ **Thin-Vane™ Air Straightener** reduces wasted airflow.



Active LED Lighting



Precise, Locking Tilt-Angles



Immediately Shore Power Ready

Our battery-driven series delivers a level of utility and performance found with no other battery-driven fan. But when you want to connect to power, Shore Power is standard on every Tempest Battery-Powered Fan that we build.



Available Options

910-1880	VS-1.3H - without battery or charger
----------	--------------------------------------

Specifications

Motor	0.87 HP / 744W Variable Speed Drive BLDC Totally Enclosed, Air over IP65
Battery	Removable HURST® Jaws of Life® E3™/EWXT™ 9Ah or 5Ah Rescue Batteries.
Charging Time	100% Charge in 2-hours with External Optional Charger
Ingress Protection	IP65 (excludes DEWALT® Batteries)
Drop Test	Designed to resist a Drop Test of 1.5M / 5'
Noise Level	83.7dB at 3m-10'
Air Volume	9,614 CFM (16,334 m³/h)
Weight	With batteries 51 lbs. / Without batteries 41 lbs.
Dimensions (L x H x D)	Handle Down - 23"L x 24.5"H x 12.5"D Handle Up +4.9"
Propeller Diameter	18"
Run Time	Average run time at full speed 35 minutes with 2 x 9AH batteries
Operating Temperature	-5°F to +113°F
Tilt Range	-12.5° to +25° with Precise Tilt Points